

FP-PRO-SYNC – Synchronic Board

The Synchronic Board allows a synchronization of up to 7 (6 + Masterplayer) Flashplayer FP-PRO-HD+. This is realized by hooking up a Masterplayer with an input extension board IOB (article FP-PRO-IOB) which again can be connected to 1, 2 or 3 Synchronic Boards. Depending on the amount of Synchronic Boards you may simultaneously operate up to 3,5 or 7 Full HD-Displays. If you need to synchronize a larger number of displays, we suggest using a RS485-HUB. Please see our Flashplayer FP-PRO-HD+ handbook for further and more detailed information.



Technical Specifications

- External connectors 2 x Sync Out (RS485), RS485-IN and RS485-OUT
- Compact metal case, 90 x 65 x 24 (W x D x H in mm), without connectors
- Working temperature 5 - 40° C, no condensing humidity
- Weight without accessories 120 gram
- Operating voltage will be supplied by Flashplayer FP-PRP-HD+ (via FP-PRO-IOB)

Areas of Application and Operation

- Synchronization from up to 7 Full-HD displays (1080p, 1920 x 1080 pixel)

Further Information

Content of Delivery: Synchronic Board

Packaging: Paperboard container

Adapter cables must be ordered separately. Technical modifications and errors reserved.