

Low-Cost Flashplayer for Long-Term Operation

The heddier Flashplayer FP-500 is the ideal playback device for audio, video and image applications. The Flashplayer FP-500 is the ultimate solution for long-term operations owing to its compact construction form as well as its robust metal case with integrated cooling fins and mounting angles. In contrast to regular PCs and HD Players, the Flashplayer FP-500 does without any kind loose parts such as fans and hard drives. Hence, nothing stand in the way of operating 24/7.

Like other Flashplayers made by heddier, the FP-500 is able to play data from miscellaneous media. In addition to CF-Card, MM-Card and USB-Stick the FP-500 also plays SD-Cards as known from digital cameras. Further highlights are the already integrated VGA interface, the remote included in the delivery and the convenient on-screen-menu.

Technical Specifications

- High-performance Flashplayer for play-back of image, audio and video files
- Plays MPEG1 and MPEG2 videos with a high-class resolution and different formats
- Playback of MP3 audio files (Equalizer Display)
- Playback of images and pictures in JPEG format with first-class text quality
- Supported storage media: CF-Card, SD-Card, MM-Card and USB-Stick
- Output for FBAS-Video and Stereo-Audio via cinch-socket
- VGA and Component-Video-Output (YPbPr) via 15-pole DSUB-socket
- 8 x Digital Input (Low-Actice)
- Timer and calendar control, various loop options, auto-run and much more



- Playback device for audio, video and image stations
- Video player for museums, exhibitions, and store furnishing (suitable for 24/7)
- Video info-terminal for store windows and sales displays
- Interactive playback system for theme-, amusement-, and sports parks
- Playback device for sound effects

Technical Features at a Glance

Video Output:	MPEG1 and MPEG2, 16:9 and 4:3, max. 720 x 480 Px
Image Output:	JPEG, 16:9 max. 1280 x 720 Px, 4:3 max, 1024 x 768 Px
	Excellent playback of texts!
Audio Output:	MP3, stereo, max 320 kBit/sec
Storage Media:	CF-Card, MM-Card, SD-Card and USB-Stick
Audio Outputs:	NF-Line Out Stereo (2 V p/p) on cinch socket
Video Outputs:	FBAS on cinch socket, component video und VGA analog on DSUB15-socket
Operating Voltage:	12 Volt DC, max. 2 ampere, main adapter 230 Volt, 50 Hz
Sized and Weight:	W147 x D129 x H40 in mm without main adapter, 350 grams
Scope Delivers:	Flashplayer FP-500, remote control and connecting cable

Technical modifications and errors reserved.

heddier Flashplayer FP-500

heddier electronic

Gesellschaft für innovative Datensysteme mbH

Pascherhook 34
D-48653 Coesfeld

Tel. +49 (0)2546 911-0

www.heddier.com
info@heddier.com

Fax +49 (0)2546 911-29